GRAS 43AI

CCP Ear Simulator for Production Testing Based on ITU-T Rec. P57 Type 3.2 High-leak





Connection: 0 V/CCP Volume: Complex

Dyn range: 25 dB(A) to 150 dB

ANSI: S3.7

The GRAS 43Al ear simulator with TEDS consists of the ITU-T Rec. P.57 Type 2 Ear Simulator and Type 3.2 Simplified High-leak Pinna Simulator and is designed for making ITU-T standardized tests of telephone handsets, receivers and receiver/loudspeaker-modules on the production line.



Technology

GRAS 43AI CCP Ear Simulator for Production Testing Based on ITU-T Rec. P57 Type 3.2 Highleak

43Al consists of the ITU-T Rec. P57 Type 2 Ear Simulator and Type 3.2 Simplified High-leak Pinna Simulator for testing leak tolerant receivers

Besides the ear and pinna simulators, GRAS 43AI includes a detachable front-plate that can be machined to make well-defined testing on various receiver related items. A calibration adapter to be used with GRAS 42AA Pistonphone/GRAS 42AP Pistonphone is included.

TEDS Compatibility

43AI is IEEE 1451.4 TEDS v. 1.0 compliant. If your measurement platform supports Transducer Electronic Data Sheets (TEDS), you will be able to read and write data like properties and calibration data.



Specifications

GRAS 43AI CCP Ear Simulator for Production Testing Based on ITU-T Rec. P57 Type 3.2 Highleak

Theoretical dynamic range lower limit with GRAS preamplifier	dB(A)	25
Theoretical dynamic range upper limit with GRAS CCP preamplifier	dB	150
Set sensitivity @ 250 Hz (±2 dB)	mV/Pa	12
Set sensitivity @ 250 Hz (±2 dB)	dB re 1V/Pa	-38.5
Coupler volume	mm³	1260 @ 500 Hz
Resonance frequency	kHz	1.570
Temperature range, operation	°C / °F	-30 to 60 / -22 to 140
Temperature coefficient @250 Hz	dB/°C / dB/°F	-0.01/-0.006
Humidity range non condensing	% RH	0 to 80
ANSI standard		S3.7
ITU-T recommondations		P.57
CE/RoHS compliant/WEEE registered		Yes/Yes/Yes
Connector type		Microdot 10/32
Weight	g / oz	0.8 / 28.219

GRAS Sound & Vibration reserves the right to change specifications and accessories without notice.



Included

GRAS RA0045- S1	Prepolarized Ear Simulator According to IEC 60318-4 (60711)
GRAS 26CB	¼" CCP Preamplifier
RS0010	Generic Adapter Ring
RA0119	Pistonphone Adapter

Optional

<u>GRAS AA0070</u>	3 m Microdot - BNC cable

GRAS Sound & Vibration reserves the right to change specifications and accessories without notice.



GRAS Worldwide

Subsidiaries and distributors in more than 40 countries

HEAD OFFICE, DENMARK

GRAS SOUND & VIBRATION

Skovlytoften 33 2840 Holte Denmark Tel: +45 4566 4046 www.GRASacoustics.com gras@grasacoustics.com

USA

GRAS SOUND & VIBRATION

9290 SW Nimbus Avenue Beaverton, OR 97008 Tel: 503-627-0832 Toll Free: 800-231-7350 www.GRASacoustics.com sales-usa@grasacoustics.com

UK

GRAS SOUND & VIBRATION

Unit 115, Gibson House, Ermine Business Park, Huntingdon, Cambridgeshire, PE29 6XU Tel: +44 (0) 7762 584 202 www.GRASacoustics.com sales-uk@grasacoustics.com

CHINA

GRAS SOUND & VIBRATION

Room 315, RuiBo Center(T1) Lane683, Shenhong Rd, Minhang District, Shanghai, China, 201107 Tel: +86 21 64203370 www.GRASacoustics.cn cnsales@grasacoustics.com



About GRAS Sound & Vibration

GRAS is a worldwide leader in the sound and vibration industry. We develop and manufacture state-of-the-art measurement microphones and related equipment for industries where acoustic measuring accuracy and repeatability are of the utmost importance. This includes applications and solutions for customers within the fields of aerospace, automotive, audiology, consumer electronics and other highly demanding industries. GRAS microphones are designed to live up to the high quality, durability and accuracy that our customers have come to expect, trust and require.

GRAS Sound & Vibration is represented through subsidiaries and distributors in more than 40 countries and is part of Axiometrix Solutions, a leading test solutions provider comprised of globally recognized measurement brands. Read more at www.grasacoustics.com

GRAS

An Axiometrix Solutions Brand

grasacoustics.com