

GRAS RA0045-S5

Externally Polarized Ear Simulator Based on IEC 60318-4 (60711), High Pressure



Standards: IEC 60318-4 (based on), ITU-T P.57

Eff vol: 1260 mm³ @ 500 Hz

Res freq: 13.5 kHz \pm 1 kHz

The GRAS RA0045-S5 Ear Simulator is an ear simulator with an acoustic input impedance closely resembling that of an average human ear. The RA0045 includes a 40BP pressure microphone and each RA0045-S5 is individually calibrated with this specific microphone.

Introduction

The RA0045-S5 Externally Polarized Ear Simulator is a special type of ear simulator for making high level acoustic measurements on earphones coupled to the human ear by ear inserts such as tubes, ear moulds, or ear tips. It has an input impedance closely resembling that of an average human ear, and, as a result, loads a sound source in very much the same way.

It is based on the following international requirements:

- IEC 60318-4: Occluded-ear simulator for the measurement of earphones coupled to the ear by ear inserts.
- ITU-T Recommendations P.57 (08/96) Series P: Telephone transmission quality, Objective measuring apparatus: Artificial ears.

Design

The RA0045-S5 embodies a number of carefully designed volumes connected via well-defined and precisely tuned resistive grooves. In an equivalent electrical circuit, capacitors would represent the volumes, and inductance and resistance would represent respectively air mass and air flow within the resistive grooves.

It is delivered with a built-in [GRAS 40BP](#) 1/4" Ext. Polarized Pressure Microphone and an individual calibration chart for the ear simulator.

Typical Applications and Use

The RA0045-S5 is for measurements on earphones and hearing aids coupled to the human ear by ear inserts such as tubes, ear moulds, or ear tips.

In accordance with ITU-T Recommendation P.57, it can be used with the following GRAS pinna simulators for testing telephones:


- [GRAS RA0056](#) Low-leak Pinna Simulator
- [GRAS RA0057](#) High-leak Pinna Simulator

A comprehensive range of accessories for making measurements in accordance with IEC 60318-4 are available. See the tab Ordering info.

Compatibility

RA0045-S5 can be used with a standard 1/4" preamplifier, e.g. [GRAS 26AC-1](#) 1/4" Standard Preamplifier with 3 m Integrated Cable.

Polarization/Connection		200 V / Traditional
Theoretical dynamic range lower limit with GRAS preamplifier	dB(A)	34
Theoretical dynamic range upper limit with GRAS preamplifier @ +120 V / ±60 V power supply	dB	164
Resonance frequency	kHz	13.5
Coupler volume	mm ³	1260 @ 500 Hz
Temperature range, operation	°C / °F	-30 to 60 / -22 to 140
Humidity range non condensing	% RH	0 to 75
ANSI standard		S3.7
IEC standard		Based on 60318-4
ITU-T recommondations		P.57 Type 2
CE/RoHS compliant/WEEE registered		Yes/Yes, Yes
Weight	g / oz	52 /1.8



Typical frequency response

GRAS Sound & Vibration reserves the right to change specifications and accessories without notice.

Optional items

GRAS RA0088	In Ear Adapter
GRAS GR0433	Calibration Adapter
GRAS GR0434	Stop Washer
GRAS GR0436	Tube Adapter
GRAS GR0437	Ear-mould Simulator
GRAS GR0438	Retention Ring
GRAS GR0440	Tube Adapter
GRAS RA0056	Low-leak Pinna Simulator
GRAS RA0057	High-leak Pinna Simulator
GRAS 26AC-1	26AC 1/4" Standard Preamp with 3 m Integrated Cable

GRAS Sound & Vibration reserves the right to change specifications and accessories without notice.

GRAS Worldwide

Subsidiaries and distributors in more
than 40 countries

HEAD OFFICE, DENMARK
GRAS SOUND & VIBRATION
Skovlytoften 33
2840 Holte
Denmark
Tel: +45 4566 4046
www.grasacoustics.com
gras@grasacoustics.com

USA
GRAS SOUND & VIBRATION
5750 S.W. Arctic Drive
Beaverton, OR 97005
Tel: 503-627-0832
Toll Free: 800-231-7350
www.grasacoustics.com
sales-usa@grasacoustics.com

UK
GRAS SOUND & VIBRATION
Unit 115, Gibson House,
Ermine Business Park, Huntingdon,
Cambridgeshire, PE29 6XU
Tel: +44 (0) 7762 584 202
www.grasacoustics.com
sales-uk@grasacoustics.com

CHINA
GRAS SOUND & VIBRATION
Room 303, Building T6
Hongqiaohui, 990, Shenchang Road
Minhang District, Shanghai
China. 201106
Tel: +86 21 64203370
www.grasacoustics.cn
cnsales@grasacoustics.com



About GRAS Sound & Vibration

GRAS is a worldwide leader in the sound and vibration industry. We develop and manufacture state-of-the-art measurement microphones and related equipment for industries where acoustic measuring accuracy and repeatability are of the utmost importance. This includes applications and solutions for customers within the fields of aerospace, automotive, audiology, consumer electronics and other highly demanding industries. GRAS microphones are designed to live up to the high quality, durability and accuracy that our customers have come to expect, trust and require.

GRAS Sound & Vibration is represented through subsidiaries and distributors in more than 40 countries and is part of Axiometrix Solutions, a leading test solutions provider comprised of globally recognized measurement brands. Read more at www.grasacoustics.com

grasacoustics.com

GRAS
An Axiometrix Solutions Brand