

GRAS 44AB

Mouth Simulator according to ITU-T Rec. P51



ITU-T rec.: P.51
IEEE standards: 269, 661

GRAS 44AB Mouth Simulator is a sound source that simulates the sound field around the human mouth at close quarters and complies with the Standards IEEE 269, 661 and ITU-T Rec. P51.

GRAS 44AB is for testing telephone mouthpieces as well as other microphones similarly used in communication networks.

GRAS 44AB and 44AB-1

At the mouth reference point (MRP), which is 25 mm from the detachable lip ring (35 mm from the mouth of the Type 44AB/AB-1), the maximum continuous signal it can produce in $\frac{1}{3}$ -octave bands is 100 dB re. 20 μ Pa in the frequency range of 100 Hz to 16 kHz. Its loudspeaker accepts an external signal directly via a BNC input.

Jigs are included for calibration according to CCITT P.51 and IEEE 269. These are for use with $\frac{1}{4}$ or $\frac{1}{2}$ microphones. One jig holds the microphone at 0° incidence ($\frac{1}{4}$ only) to the sound source, the other at 90° incidence ($\frac{1}{4}$ or $\frac{1}{2}$).


NOTE: This type of mouth simulator can not be mounted inside a KEMAR head.

Connector type		BNC
ITU-T recommendations		P.51
IEEE standard		269, 661
Maximum power, continuous	W	10
Maximum power, pulsed 2 sec.	W	50
Temperature range, operation	°C / °F	10 to 35 / 50 to 95
CE/RoHS compliant/WEEE registered		Yes/Yes/Yes
Weight	g / oz	1000 / 35.274

Maximum continuous output level at MRP [200 Hz - 6 kHz] 110 dB re. 20 Pa

Maximum continuous output level at MRP [100 Hz - 16 kHz] 100 dB re. 20 Pa

Distortion 250 Hz - 8 kHz (Linear signal @ 94 dB at MRP) typically 1 %, max. 1.5 %



Frequency response

GRAS Sound & Vibration reserves the right to change specifications and accessories without notice.

Included

GRAS RA0104	Jig (CCITT P51)
GRAS RA0105	Jig (IEEE 269)

Optional

GRAS RA0110	Conical mouthpiece
-------------	--------------------

GRAS Sound & Vibration reserves the right to change specifications and accessories without notice.

GRAS Worldwide

Subsidiaries and distributors in more
than 40 countries

HEAD OFFICE, DENMARK
GRAS SOUND & VIBRATION
Skovlytoften 33
2840 Holte
Denmark
Tel: +45 4566 4046
www.GRASacoustics.com
gras@grasacoustics.com

USA
GRAS SOUND & VIBRATION
9290 SW Nimbus Avenue
Beaverton, OR 97008
Tel: 503-627-0832
Toll Free: 800-231-7350
www.GRASacoustics.com
sales-usa@grasacoustics.com

UK
GRAS SOUND & VIBRATION
Unit 115, Gibson House,
Ermine Business Park, Huntingdon,
Cambridgeshire, PE29 6XU
Tel: +44 (0) 7762 584 202
www.GRASacoustics.com
sales-uk@grasacoustics.com

CHINA
GRAS SOUND & VIBRATION
Room 315, RuiBo Center(T1)
Lane683, Shenhong Rd,
Minhang District,
Shanghai, China, 201107
Tel: +86 21 64203370
www.GRASacoustics.cn
cnsales@grasacoustics.com



About GRAS Sound & Vibration

GRAS is a worldwide leader in the sound and vibration industry. We develop and manufacture state-of-the-art measurement microphones and related equipment for industries where acoustic measuring accuracy and repeatability are of the utmost importance. This includes applications and solutions for customers within the fields of aerospace, automotive, audiology, consumer electronics and other highly demanding industries. GRAS microphones are designed to live up to the high quality, durability and accuracy that our customers have come to expect, trust and require.

GRAS Sound & Vibration is represented through subsidiaries and distributors in more than 40 countries and is part of Axiometrix Solutions, a leading test solutions provider comprised of globally recognized measurement brands. Read more at www.grasacoustics.com

grasacoustics.com

GRAS
An Axiometrix Solutions Brand