GRAS 26AG

1/2" Insert Voltage Preamplifier with Integrated Connector





Freq range: 2.5 Hz - 200 kHz

Noise: 1.8 µV Gain: -0.25 dB

Special feature: Insert voltage for determining open-circuit sensitivity of a

microphone

The GRAS 26AG is a small robust preamplifier with insert voltage calibration facility. It has a very low inherent noise level, a wide dynamic range and a frequency response from below 2 Hz to above 200 kHz.



Technology

Typical application & use


Precision measurements

Low-pressure measurements

General-purpose preamplifiers

Design

All GRAS microphone preamplifiers are based on a small ceramic thick film substrate with a very high input impedance. The ceramic substrate is shielded by a guard ring to minimise the influence of stray capacitance and microphonic interference. The casing is made of stainless steel for maximum strength and durability. The small dimensions of the 26AG preamplifier ensures reliable operation under humid conditions owing to the heat generated by internal power dissipation.



7-pin LEMO 1B male (ext. view)

Connector

Compatibility

The 26AG preamplifier is compatible with ½-inch microphones as defined in international standard IEC1094 Measurement Microphones, Part 4: Specifications for working standard microphones. The mounting thread (11.7 mm - 60 UNS-2) is compatible with other available makes of similar microphone preamplifiers.

The 26AG is integrated with a 7-pin LEMO series 1B plug and comes with an insert-voltage calibration facility for determining the open-circuit sensitivity of condenser microphones.

Connector



Specifications


GRAS 26AG 1/2" Insert Voltage Preamplifier with Integrated Connector

Frequency range (±0.2 dB) with 18 pF microphone dummy	Hz	2.5 to 200 k
Slew rate	V/μs	20
Input impedance	GΩ // pF	20 // 0.4
Output impedance	Ω	75
Output Voltage Swing, max. @ ±14V/+28V power supply	Vp	12
Output Voltage Swing, max. @ ±60V/+120V power supply	Vp	50
Noise (A-Weighted) max.	μV	2.5
Noise (A-Weighted) typ.	μV	1.8
Noise (Linear 20 Hz – 20 kHz) max.	μV	6
Noise (Linear 20 Hz – 20 kHz) typ.	μV	3.5
Gain	dB	-0.25
Power supply, single	V	28 to 120
Power supply, balanced	V	±14 to ±60
DC-offset, min., single suppy	V	0.5 x Vs - 1
DC-offset, max., single suppy	V	0.5 x Vs + 4
DC-offset, balanced supply	V	-1 to 4
Temperature range, operation	°C / °F	-30 to 70 / -22 to 158
Temperature range, storage	°C / °F	-40 to 85 / -40 to 185
Humidity range non condensing	% RH	0 to 95
Connector type		7-pin LEMO (FGG.1B.307)
CE/RoHS compliant/WEEE registered		Yes / Yes, Yes
Weight	g / oz	34.0 / 1.24

Conditions: 23 °C Ambient temperature, $\pm 60 \text{V}/\pm 120 \text{V}$ power supply, 18 pF dummy microphone, 3 m output cable.




Specifications



Low frequency response for various microphone capacities



Specifications




Max. RMS output signal for various cable loads with 120 V supply


GRAS Sound & Vibration reserves the right to change specifications and accessories without notice.



Dimensions

Dimensions in mm







Ordering info

Optional items

GRAS AA0008

3 m LEMO 7-pin - LEMO 7-pin Cable

GRAS Sound & Vibration reserves the right to change specifications and accessories without notice.



GRAS Worldwide

Subsidiaries and distributors in more than 40 countries

HEAD OFFICE, DENMARK

GRAS SOUND & VIBRATION

Skovlytoften 33 2840 Holte Denmark Tel: +45 4566 4046 www.GRASacoustics.com gras@grasacoustics.com

USA

GRAS SOUND & VIBRATION

9290 SW Nimbus Avenue Beaverton, OR 97008 Tel: 503-627-0832 Toll Free: 800-231-7350 www.GRASacoustics.com sales-usa@grasacoustics.com

UK

GRAS SOUND & VIBRATION

Unit 115, Gibson House, Ermine Business Park, Huntingdon, Cambridgeshire, PE29 6XU Tel: +44 (0) 7762 584 202 www.GRASacoustics.com sales-uk@grasacoustics.com

CHINA

GRAS SOUND & VIBRATION

Room 315, RuiBo Center(T1) Lane683, Shenhong Rd, Minhang District, Shanghai, China, 201107 Tel: +86 21 64203370 www.GRASacoustics.cn cnsales@grasacoustics.com



About GRAS Sound & Vibration

GRAS is a worldwide leader in the sound and vibration industry. We develop and manufacture state-of-the-art measurement microphones and related equipment for industries where acoustic measuring accuracy and repeatability are of the utmost importance. This includes applications and solutions for customers within the fields of aerospace, automotive, audiology, consumer electronics and other highly demanding industries. GRAS microphones are designed to live up to the high quality, durability and accuracy that our customers have come to expect, trust and require.

GRAS Sound & Vibration is represented through subsidiaries and distributors in more than 40 countries and is part of Axiometrix Solutions, a leading test solutions provider comprised of globally recognized measurement brands. Read more at www.grasacoustics.com

GRAS

An Axiometrix Solutions Brand

grasacoustics.com