

# GRAS 43AA-S2

CCP Ear Simulator Kit According to IEC 60318-1 & -2



Connection: 0 V/CCP

Volume: Complex

Dyn range: 25 dB(A) to 150 dB

ANSI: S3.7

IEC: 60318-1 & -2

The GRAS 43AA-S2 CCP Ear Simulator Kit with TEDS is a complete test jig for acoustical measurements on telephone handsets and earphones. It includes an IEC 60318 Ear Simulator RA0039 which is individually calibrated according to the ITU-T Recommendation P.57 (08/96) "Series P: Telephone transmission quality, objective measuring apparatus: artificial ears."

The GRAS 43AA-S2 CCP Ear Simulator Kit according to IEC 60318-1 & -2 is a complete test jig for acoustical measurements on telephone handsets and earphones in accordance with:

- IEC60318-1 & -2 Electroacoustics – Simulators of human head and ear – Part 1: Ear simulator for the calibration of supraaural earphones, 1998-07
- ITU-T Recommendation P.57 (08/96) Series P: Telephone transmission Quality, Objective measuring apparatus: Artificial Ears

It consists of the following components:

- IEC 60318-1 & -2 [GRAS RA0039 Ear Simulator](#)
- [GRAS 40AO ½" Pressure Microphone](#)
- [GRAS 26CB ¼" Preamplifier](#)
- [GRAS RA0052 Test Jig](#)
- Mounting plates for circum-aural and supra-aural headphones

The Test Jig has an adjustable spring-loaded arm to exert a variable force on the test object.

An externally polarized version is available, [GRAS 43AA](#).

A version with a [GRAS 26AB](#). Preamplifier is available, [GRAS 43AA-S3](#).

## TEDS Compatibility

43AA-S2 is IEEE 1451.4 TEDS v. 1.0 compliant. If your measurement platform supports Transducer Electronic Data Sheets (TEDS), you will be able to read and write data like properties and calibration data.

# Specifications

Theoretical dynamic range lower limit with GRAS preamplifier	dB(A)	25
Theoretical dynamic range upper limit with GRAS CCP preamplifier	dB	150
Set sensitivity @ 250 Hz ( $\pm 3$ dB)	mV/Pa	12
Set sensitivity @ 250 Hz ( $\pm 3$ dB)	dB re 1V/Pa	-38.5
Temperature range, operation	°C / °F	-30 to 60 / -22 to 140
Temperature coefficient @250 Hz	dB/°C / dB/°F	-0.01 / -0.006
Humidity range non condensing	% RH	0 to 80
ANSI standard		S3.7
ITU-T recommendations		P.57 Type 1
CE/RoHS compliant/WEEE registered		Yes/Yes/Yes
Connector type		BNC
Weight	g / oz	1.65 / 58.202

GRAS Sound & Vibration reserves the right to change specifications and accessories without notice.

## Included items

[GRAS AA0070](#)

3 m Microdot - BNC Cable

## Optional items

[GRAS RA0196](#)

Retrofit High-tension Spring Kit for RA0052 (for previous versions (before summer 2014))

GRAS Sound & Vibration reserves the right to change specifications and accessories without notice.

# GRAS Worldwide

Subsidiaries and distributors in more than 40 countries

## HEAD OFFICE, DENMARK

**GRAS SOUND & VIBRATION**  
Skovlytoften 33  
2840 Holte  
Denmark  
Tel: +45 4566 4046  
[www.GRASacoustics.com](http://www.GRASacoustics.com)  
[gras@grasacoustics.com](mailto:gras@grasacoustics.com)

## USA

**GRAS SOUND & VIBRATION**  
9290 SW Nimbus Avenue  
Beaverton, OR 97008  
Tel: 503-627-0832  
Toll Free: 800-231-7350  
[www.GRASacoustics.com](http://www.GRASacoustics.com)  
[sales-usa@grasacoustics.com](mailto:sales-usa@grasacoustics.com)

## UK

**GRAS SOUND & VIBRATION**  
Unit 115, Gibson House,  
Ermine Business Park, Huntingdon,  
Cambridgeshire, PE29 6XU  
Tel: +44 (0) 7762 584 202  
[www.GRASacoustics.com](http://www.GRASacoustics.com)  
[sales-uk@grasacoustics.com](mailto:sales-uk@grasacoustics.com)

## CHINA

**GRAS SOUND & VIBRATION**  
Room 315, RuiBo Center(T1)  
Lane683, Shenhong Rd,  
Minhang District,  
Shanghai, China, 201107  
Tel: +86 21 64203370  
[www.GRASacoustics.cn](http://www.GRASacoustics.cn)  
[cnsales@grasacoustics.com](mailto:cnsales@grasacoustics.com)



## About GRAS Sound & Vibration

GRAS is a worldwide leader in the sound and vibration industry. We develop and manufacture state-of-the-art measurement microphones and related equipment for industries where acoustic measuring accuracy and repeatability are of the utmost importance. This includes applications and solutions for customers within the fields of aerospace, automotive, audiology, consumer electronics and other highly demanding industries. GRAS microphones are designed to live up to the high quality, durability and accuracy that our customers have come to expect, trust and require. GRAS Sound & Vibration is represented through subsidiaries and distributors in more than 40 countries and is part of Axiometrix Solutions, a leading test solutions provider comprised of globally recognized measurement brands. Read more at [www.grasacoustics.com](http://www.grasacoustics.com)

[grasacoustics.com](http://grasacoustics.com)

**GRAS**  
An Axiometrix Solutions Brand