

GRAS 43AH

CCP Ear Simulator for Production Testing Based on ITU-T
Rec. P57 Type 3.2 Low-leak



Connection: 0 V/CCP
Volume: Complex
Dyn range: 25 dB(A) to 150 dB
ANSI: S3.7
IEC: 60318-1 & -2

This GRAS 43AH ear simulator with TEDS consists of the ITU-T Rec. P.57 Type 2 Ear Simulator and Type 3.2 Simplified Low-leak Pinna Simulator and is designed for making ITU-T standardized tests of telephone handsets, receivers and receiver/loudspeaker-modules on the production line.

43AH consists of the ITU-T Rec. P57 Type 2 Ear Simulator and Type 3.2 Simplified Low-leak Pinna Simulator and is designed for making ITU-T standardized tests of telephone handsets, receivers and receiver/loudspeaker modules on the production line.

Besides the ear and pinna simulators, GRAS 43AH includes a detachable front-plate that can be machined to make well-defined testing on various receiver related items. A calibration adapter to be used with [GRAS 42AA Pistonphone](#)/[GRAS 42AP Pistonphone](#) is included.

43AH can also be delivered with customized front plates that will enable leakage-controlled testing according to your specific needs.

TEDS Compatibility

43AH is IEEE 1451.4 TEDS v. 1.0 compliant. If your measurement platform supports Transducer Electronic Data Sheets (TEDS), you will be able to read and write data like properties and calibration data.

Theoretical dynamic range lower limit with GRAS preamplifier	dB(A)	25
Theoretical dynamic range upper limit with GRAS CCP preamplifier	dB	150
Set sensitivity @ 250 Hz (± 2 dB)	mV/Pa	12
Set sensitivity @ 250 Hz (± 2 dB)	dB re 1V/Pa	-38.5
Coupler volume	mm ³	1260 @ 500 Hz
Resonance frequency	kHz	0.713
Temperature range, operation	°C / °F	-30 to 60 / -22 to 140
Temperature coefficient @250 Hz	dB/°C / dB/°F	-0.01 / -0.006
Humidity range non condensing	% RH	0 to 80
ANSI standard		S3.7
ITU-T recommendations		P.57 Type 1
CE/RoHS compliant/WEEE registered		Yes/Yes/Yes
Connector type		3 m 7-pin LEMO
Weight	g / oz	0.8 / 28.219

GRAS Sound & Vibration reserves the right to change specifications and accessories without notice.

Included

GRAS RA0045-S1	IEC 60711 Ear Simulator, Prepol.
GRAS 26CB	¼" CCP Preamplifier
RS0010	Generic Adapter Ring
RA0119	Pistonphone Adapter

Miscellaneous

GRAS RA0196	High-tension springs (set of two)
-----------------------------	-----------------------------------

GRAS Sound & Vibration reserves the right to change specifications and accessories without notice.

GRAS Worldwide

Subsidiaries and distributors in more
than 40 countries

HEAD OFFICE, DENMARK
GRAS SOUND & VIBRATION
Skovlytoften 33
2840 Holte
Denmark
Tel: +45 4566 4046
www.GRASacoustics.com
gras@grasacoustics.com

USA
GRAS SOUND & VIBRATION
9290 SW Nimbus Avenue
Beaverton, OR 97008
Tel: 503-627-0832
Toll Free: 800-231-7350
www.GRASacoustics.com
sales-usa@grasacoustics.com

UK
GRAS SOUND & VIBRATION
Unit 115, Gibson House,
Ermine Business Park, Huntingdon,
Cambridgeshire, PE29 6XU
Tel: +44 (0) 7762 584 202
www.GRASacoustics.com
sales-uk@grasacoustics.com

CHINA
GRAS SOUND & VIBRATION
Room 315, RuiBo Center(T1)
Lane683, Shenhong Rd,
Minhang District,
Shanghai, China, 201107
Tel: +86 21 64203370
www.GRASacoustics.cn
cnsales@grasacoustics.com



About GRAS Sound & Vibration

GRAS is a worldwide leader in the sound and vibration industry. We develop and manufacture state-of-the-art measurement microphones and related equipment for industries where acoustic measuring accuracy and repeatability are of the utmost importance. This includes applications and solutions for customers within the fields of aerospace, automotive, audiology, consumer electronics and other highly demanding industries. GRAS microphones are designed to live up to the high quality, durability and accuracy that our customers have come to expect, trust and require.

GRAS Sound & Vibration is represented through subsidiaries and distributors in more than 40 countries and is part of Axiometrix Solutions, a leading test solutions provider comprised of globally recognized measurement brands. Read more at www.grasacoustics.com

grasacoustics.com

GRAS
An Axiometrix Solutions Brand