

# GRAS RA0016

20 dB Attenuator for externally polarized 1/2" microphones



Length: 47.5 mm  
Diam.: 12.70 mm

**Recommendation:** Choose a microphone with low sensitivity instead of using the RA0016.

The RA0016 is a 20 dB attenuator for inserting between a 1/2" microphone and preamplifier. It will attenuate the output signal of the microphone by 20 dB in order to avoid overloading the preamplifier. The RA0016 is useful when measuring very high sound pressure levels using a preamplifier with limited dynamic range.

The RA0016 will work properly only with externally polarized microphones. For prepolarized microphones, use the RA0018.

**Recommendation:** Choose a microphone with low sensitivity instead of using the RA0016.

## Introduction

The GRAS RA0016 is a 20 dB attenuator for inserting between a 1/2" microphone and preamplifier. It will attenuate the output signal of the microphone by 20 dB in order to avoid overloading the preamplifier.

The RA0016 is useful when measuring very high sound pressure levels using a preamplifier with limited dynamic range. The RA0016 will work properly only with externally polarized microphones. For prepolarized microphones, use the RA0018.

## Design

For precision measurements, the actual combination of microphone, attenuator and preamplifier should be calibrated with a precision calibrator like GRAS 42AA Pistonphone. The attenuation of the microphone signal is obtained by a capacitive voltage divider, and depends on both the microphone capacity and the preamplifier input impedance. The attenuation has been adjusted to 20 dB with a microphone with 20 pF capacity and with a typical GRAS preamplifier.

## Quality & Warranty

GRAS accessories are made of stainless steel, alloys and high-quality composites. These items are covered by a 2 year warranty respecting their intended use.

On consumables like batteries, cables and windscreens we offer a 6 month warranty.



# GRAS Worldwide

Subsidiaries and distributors in more  
than 40 countries

## HEAD OFFICE, DENMARK

### GRAS SOUND & VIBRATION

Skovlytoften 33  
2840 Holte  
Denmark  
Tel: +45 4566 4046  
[www.GRASacoustics.com](http://www.GRASacoustics.com)  
[gras@grasacoustics.com](mailto:gras@grasacoustics.com)

## USA

### GRAS SOUND & VIBRATION

9290 SW Nimbus Avenue  
Beaverton, OR 97008  
Tel: 503-627-0832  
Toll Free: 800-231-7350  
[www.GRASacoustics.com](http://www.GRASacoustics.com)  
[sales-usa@grasacoustics.com](mailto:sales-usa@grasacoustics.com)

## UK

### GRAS SOUND & VIBRATION

Unit 115, Gibson House,  
Ermine Business Park, Huntingdon,  
Cambridgeshire, PE29 6XU  
Tel: +44 (0) 7762 584 202  
[www.GRASacoustics.com](http://www.GRASacoustics.com)  
[sales-uk@grasacoustics.com](mailto:sales-uk@grasacoustics.com)

## CHINA

### GRAS SOUND & VIBRATION

Room 315, RuiBo Center(T1)  
Lane683, Shenhong Rd,  
Minhang District,  
Shanghai, China, 201107  
Tel: +86 21 64203370  
[www.GRASacoustics.cn](http://www.GRASacoustics.cn)  
[cnsales@grasacoustics.com](mailto:cnsales@grasacoustics.com)



## About GRAS Sound & Vibration

GRAS is a worldwide leader in the sound and vibration industry. We develop and manufacture state-of-the-art measurement microphones and related equipment for industries where acoustic measuring accuracy and repeatability are of the utmost importance. This includes applications and solutions for customers within the fields of aerospace, automotive, audiology, consumer electronics and other highly demanding industries. GRAS microphones are designed to live up to the high quality, durability and accuracy that our customers have come to expect, trust and require.

GRAS Sound & Vibration is represented through subsidiaries and distributors in more than 40 countries and is part of Axiometrix Solutions, a leading test solutions provider comprised of globally recognized measurement brands. Read more at [www.grasacoustics.com](http://www.grasacoustics.com)

[grasacoustics.com](http://grasacoustics.com)

**GRAS**  
An Axiometrix Solutions Brand